



## RWG500

### INTELLIGENT AND SILENT REWINDER

#### FEATURES

- /// Auto-adjustable winding speed corresponds to the label print speed
- /// Noise level below 60dB
- /// Auto-adjustable winding
- /// User-friendly operation panel
- /// Up to 6" label with support

# TECHNICAL INFORMATION

## RWG500

OPERATION CHARACTERISTICS		
Environment	Operating	0 ~ 40°C / 30 ~ 80% (without condensation)
	Storage	-5 ~ 60°C / 30 ~ 90% (without condensation)
Regulatory approvals	UL/C-UL, FCC, CE, TUV, CCC	
Dimension (W x D x H)	280 mm x 320 mm x 230 mm	
Weight	7.5KG	
Noise level	Less than 60dB	
Input power	DC_24V, 2A	
Printer connection	Connection cable dedicated for SATO PRINTER: EXT cable joint plate: Yes (supports following models as standard) (M5900Rve / CL4xxe / M84Pro / GTe4xxe / CL6xxe) (CL6xxe can be used only when media width is 131 mm or less)	

WINDING CHARACTERISTICS		
Winding speed	Maximum 381 mm / sec (max. 15 inch / sec)	
Winding method	External winding: direct on the 40 mm spindle / 3 inch paper core winding	
Winding direction	Fac-out / Face-in (Counterclockwise / Clockwise)	
Winding monitoring	Winding ON / OFF by tension are position	
Winding outer diameter	Maximum winding OD up to 265 mm (11 inch)	
Media size	Width, mm	25 - 131 (option 132 - 180)
	Pitch, mm	8 - 400
	Thickness, mm	0.08 - 0.27

OPTIONS	
Accessories	Conversion kit to extend width from 4 inch to 6 inch Standalone PSU